Issue 2013.05.28 Revision 2024.09.17

Safety Data Sheet (SDS)

Section 1 - CHEMICALS AND COMPANY IDENTIFICATION

Chemical Identifier Ink-1113K/Ink-K113
Product Code I113K/JP-K113

Reference Number 37

Name of Supplier Hitachi Industrial Equipment Systems Co.,Ltd.

Address 1-1 Higashitaga-cho 1-chome,Hitachi-shi, Ibaraki-ken,

316-8502 Japan

Department in Charge IJP ink Group, Marking Systems and Hoist Systems Division

Phone Number +81-294-36-8682 Fax Number +81-294-36-8975

Mail Address aida-kohhei@hitachi-ies.co.jp

Emergency Phone

Number

Recommended Use

Industrial ink jet printers

+81-294-36-8682

recommended, seek the judgment of an expert/chemical substance

specialist, etc.

Section 2 - HAZARDS IDENTIFICATION GHS Classification of the Chemical

Physicochemical

Flammable liquids Category 2

Health Hazards Acute toxicity (Inhalation: vapour) Category 4

Acute toxicity (Inhalation: dust and mist) Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Carcinogenicity Category 2
Reproductive toxicity Category 1B

Specific target organ toxicity (single exposure) Category

2(kidney)

Specific target organ toxicity (single exposure) Category

3(narcotic effect, respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Category 1 (nervous system)

Environmental Hazards Hazardous to the aquatic environment, short-term

(acute) Category 3

Hazardous to the aquatic environment, long-term

(chronic) Category 3

Other hazards than mentioned above are Not classified

or Classification not possible.

GHS Label Elements

Pictograms



Signal Word Danger

Hazard Statements H225 Highly flammable liquid and vapour

H315 Causes skin irritation H319 Causes serious eye irritation

H332 Harmful if inhaled

H335 May cause respiratory irritation H336 May cause drowsiness or dizziness H351 Suspected of causing cancer

H360 May damage fertility or the unborn child

H371 May cause damage to kidney

H372 Causes damage to nervous system through

prolonged or repeated exposure

H412 Harmful to aquatic life with long lasting effects

Precautionary Statements

Prevention

Obtain special instructions before use.(P201)

Do not handle until all safety precautions have been

read and understood.(P202)

Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.(P210)

Keep container tightly closed.(P233)
Ground and bond container and receiving

equipment.(P240)
Use explosion-proof electrical, ventilating and lighting

equipment.(P241)
Use non-sparking tools.(P242)

Take action to prevent static discharges.(P243)

Do not breathe

dust/fume/gas/mist/vapours/spray.(P260)

Avoid breathing

dust/fume/gas/mist/vapours/spray.(P261) Wash hand thoroughly after handling.(P264) Wash eye thoroughly after handling.(P264) Do not eat, drink or smoke when using this

product.(P270)

Use only outdoors or in a well-ventilated area.(P271)

Avoid release to the environment.(P273)
Wear protective gloves/protective clothing/eye

protection/face protection.(P280)

Response

IF ON SKIN: Wash with plenty of soap and water.(P302+P352)

IF ON SKIN or hair: Take off immediately all contaminated clothing. Rinse skin with water or shower.(P303+P361+P353)

IF INHALED: Remove person to fresh air and keep

comfortable for breathing.(P304+P340)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.(P305+P351+P338)

IF exposed or concerned: Call a doctor.(P308+P311)

IF exposed or concerned: Get medical advice/attention.(P308+P313)

Call a doctor if you feel unwell.(P312)
Get medical advice and attention if you feel unwell.(P314)

Specific treatment.(P321)

If skin irritation occurs: Get medical advice/attention.(P332+P313)

If eye irritation persists: Get medical

advice/attention.(P337+P313)

Take off contaminated clothing and wash it before

reuse.(P362+P364)

In case of fire: Use appropriate media to

extinguish.(P370+P378)

Storage

Store in a well-ventilated place. Keep container tightly

closed.(P403+P233)

Store in a well-ventilated place. Keep cool.(P403+P235)

Store locked up.(P405)

Disposal Dispose of contents and container in accordance with

local, regional and national regulations (to be

specified).(P501)

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Distinction of Substance or

Mixture

Mixture

Chemical Name or Generic	Concentration or Its	Formula	ENCS No./ISHL No.		CAS RN
Name	Ranges (wt%)		ENCS No.	ISHL No.	
Methyl ethyl ketone	75-less than 85	CH3CH2CO CH3	(2)-542	Registered	78-93-3
Chromium and its compounds	3–5	-	Registered(Trade secret)	Registered(Trade secret)	_
1-Butanol	0.1-1	CH3CH2CH 2CH2OH	(2)-3049	Registered	71-36-3

Section 4 - FIRST AID MEASURES

Inhalation IF INHALED: Remove to fresh air and keep at rest in a

position comfortable for breathing.

IF exposed or concerned: Call a doctor.
Skin Contact IF ON SKIN (or hair): Remove/Take off

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice and

attention.

Specific treatment.

IF exposed or concerned: Call a doctor.

Eye Contact

IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Call a doctor.

Ingestion Rinse mouth.

IF SWALLOWED: Call a doctor if you feel unwell.

IF exposed or concerned: Call a doctor.

Section 5 - FIRE FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing agent suitable for type of surrounding

fire.

When dust occurs, use dry sand.

Unsuitable Extinguishing

Media

Specific Hazards in Case of

Fire

Specific Fire Fighting

Special Protective

for Fire Fighters

Risk of producing harmful gases such as carbon monoxide. Avoid inhalation of smoke or gases.

Fight fire from upwind position if possible Keep away from sources of ignition and use appropriate

extinguishing media.

Prohibit unauthorized staff from entering the area

around the fire.

Cylindric water.

Keep unnecessary people away.

Use goggles in combination with dust mask, and another

protections as appropriate to situation.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions,
Protective Equipment and
Emergency Procedures

Equipment and Precautions

Use goggles in combination with dust mask, and another

protections as appropriate to situation.

Large spills :Evacuate area.
Ensure adequate ventilation.

Environmental Precautions Do not discharge into the drains, surface waters or

ground water directly.

No information available

Methods and Equipment for Containment and Cleaning

Up

Storage

Prevention Measures for Secondary Accidents

Keep away from sources of ignition and prepare

extinguishing media.

Section 7 - HANDLING AND STORAGE

Handling Technical Measures

Provide ventilation system and use necessary personal protective equipment as described in "Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION".

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Use explosion-proof electrical/ventilating/lighting.

Take precautionary measures against static discharge.

Use local exhaust ventilation in case of production of

fume or mist.

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Precautions for Safe

Handling

Keep cool.

Do not breathe dust/fume/gas/mist/vapours/spray.

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye

protection/face protection.

Prevents Handling of

Incompatible Substances or Mixtures Refer to "Section 10 - STABILITY AND REACTIVITY".

Conditions for Safe

Storage

Refer to "Section 10 - STABILITY AND REACTIVITY".

Store locked up.

Store container tightly closed in well-ventilated place.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

	Japan Administration Level	Exposure Limits (Japan Society for Occupational Health)	
Methyl ethyl ketone	200ppm	200ppm(590mg/m3)	TWA 200 ppm, STEL 300 ppm
Chromium and its compounds	Not listed	0.5mg/m3 as Cr3+	Not listed
1-Butanol	25ppm	[Maximum allowable concentration:] 50ppm (150mg/m3) (skin)	TWA 20 ppm, STEL -

	Concentration standards specified by the Minister of Health, Labour and Welfare			
	Concentration standard value for 8-hours exposure	Concentration standard value for short- term exposure/ceiling		
Methyl ethyl ketone	Not listed	Not listed		
Chromium and its compounds	Not listed	Not listed		
1-Butanol	Not listed	Not listed		

Engineering Controls Use local exhaust ventilation in case of production of

fume or mist.

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Use explosion-proof electrical equipment and prevent

from static electrocity

Personal Protective

Equipment

Respiratory Protection Select and wear appropriate respiratory protective equipment based on risk assessments and other

measures.

Hand Protection Wear appropriate protective equipment, including

impervious or impermeable safety gloves, as

circumstances dictate.

Select and wear appropriate safety gloves based on risk

assessments and other measures.

Eye/Face Protection Select and wear appropriate face and eye protection

based on risk assessments and other measures.

Skin and Bodv Protection

Wear appropriate protective equipment such as impervious and impermeable protective clothing and

footwear, as circumstances dictate.

Select and wear appropriate protective clothing and footwear based on risk assessments and other

measures.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liauid Form Liquid Colour Black Odour Solvent odor

Melting Point/Freezing

Point

-86.4°C (as 2-Butanone) 79.6 °C (as 2-Butanone)

Boiling Point or Initial Boiling Point and Boiling

Ranges

Flammability Flammability

Lower and Upper Explosion Lower Limit

Limit / Flammability Limit

1.8vol% (as 2-Butanone)

Upper Limit 11.5vol% (as 2-Butanone)

Flash Point -5.2°C (Tag Closed Cup) 505°C (as 2-Butanone) Auto-Ignition Temperature

Decomposition Temperature No data available

рΗ No data available Kinematic Viscosity 3.4 mm 2/s

water: 29g/100mL (20°C) (as 2-Butanone) Solubility

Partition Coefficient : n-0.29(as 2-Butanone)

Octanol/Water

10.5kPa (20°C) (as 2-Butanone) Vapour Pressure

Density and/or Relative

Density

Relative Gas Density 2.41 (Air=1, as 2-Butanone)

Particle Characteristics No data available

as Methyl ethyl ketone

-86.4°C Melting Point/Freezing

Point

Boiling Point or Initial

Boiling Point and Boiling

Ranges

79.6°C

Density and/or Relative

Density

0.8061

as 1-Butanol

Boiling Point or Initial Boiling Point and Boiling

117.7°C

Density and/or Relative

Density

0.81337(15°C, 4°C), 0.80978(20°C, 4°C)

Stable under normal conditions of use.

Does not react dangerously under nomal conditions.

There is a risk of explosion due to impacts, friction, flame and other

Section 10 - STABILITY AND REACTIVITY

Reactivity

Chemical Stability Possibility of Hazardous

Reaction

Conditions to Avoid

Incompatible Substances or Mixtures Hazardous Decomposition

Products Other Data No data available No data available

source of ignition.

Flammable

No data available

Section 11 - TOXICOLOGICAL INFORMATION

Acute Toxicity

Oral Dermal Classification not possible since lots of the concentrations of unknown ingredients.

Classification not possible since lots of the concentrations of unknown ingredients.

Inhalation (gas)

Does not fall under gas based on GHS definitions.

(vapour)

Classified as Category 4 since ATE is 2500 to

20000(ppmV). (dust and mist)

Classified as Category 4 since ATE is 1.5mg/l. Classified as Category 2 since the sum of Category 2

ingredients is more than 10%.

Category 2A is more than 10%.

Serious Eye Damage/Eye Classified as Category 2A since the sum of Eye

Irritation

Respiratory Sensitization

Skin Corrosion/Irritation

Skin Sensitization

Germ Cell Mutagenicity

Carcinogenicity

Reproductive Toxicity

Specific Target Organ

Toxicity (Single Exposure)

Unable to classify due to insufficient data.

Unable to classify due to insufficient data.

Classification not possible since lots of the concentrations of unknown ingredients.

Classified as Category 2 since one of the Category 2

ingredients is more than 1.0%.

(Reproductive toxicity)

Classified as Category 1B since one of the Category 1B

ingredients is more than 0.3%.

(Reproductive toxicity, effects on or via lactation)

Unable to classify due to insufficient data. Classified as Category 2(kidney) since one of the Category 2(kidney) ingredients is more than 10%.

Classified as Category 3(narcotic effect) since the sum

of Category 3(narcotic effect) ingredients is more than

Classified as Category 3(respiratory tract irritation) since the sum of Category 3(respiratory tract irritation)

ingredients is more than 20%.

Specific Target Organ Toxicity (Repeated Exposure)

Aspiration Hazard

Classified as Category 1(nervous system) since one of the Category 1(nervous system) ingredients is more

than 10%.

Unable to classify due to insufficient data.

Section 12 - ECOLOGICAL INFORMATION

Hazardous to the Aquatic Environment, Short-Term

(Acute)

Hazardous to the Aquatic Environment, Long-Term (Chronic)

Ecotoxicity
Persistence
Bioaccumulative Potential

Mobility in Soil

Hazardous to the Ozone

Laver

Classified as Category 3 since the sum of (M \times 100 \times Category 1) + (10 \times Category 2) + Category 3 ingredients

is more than 25%.

Classified as Category 3 since the sum of $(M \times 100 \times Category 1) + (10 \times Category 2) + Category 3 ingredients$

is more than 25%. No data available No data available No data available

No data available

Unable to classify due to insufficient data.

Section 13 - DISPOSAL CONSIDERATIONS

Residual waste

Because waste materials such as liquid waste, paper towels used to wipe it up, or empty containers are flammable combustible materials, the section on "specially controlled industrial waste(Flammable waste oil)" from the Waste Management and Public Cleaning Law (Waste Management Law) is applicable.

Either appropriately process in accordance with Waste Management and Public Cleaning Law, or commission a contractor licensed for transport or disposal of industrial waste requiring special management.

Do not let wastewater, etc. used for cleaning machinery or containers flow directly onto the groundor in to the culverts.

For waste materials generated by wastewater treatment, incineration, etc. either carry out processingin accordance with the Waste Management and Public Cleaning Law and related laws and regulations, or commission a licensed vendor to do so.

When incinerating of waste materials, etc., do not use an incinerator without cleaning equipment, as harmful gas will be generated.

Clarify the contents of waste materials and entrust disposal to a waste disposal company.

Contaminated containers and packaging

Empty containers should be treated as industrial wastes and not

allowed to contain waste.

Section 14 - TRANSPORT INFORMATION

International Regulations

Regulatory Information Conform to the provisions of IMO.

by Sea

UN No. 12

Proper Shipping Name PRINTING INK RELATED MATERIAL

Class 3 Packing Group II

Marine Pollutant Not applicable Liquid Substance Not applicable

Transported in Bulk According to MARPOL 73/78, Annex II, the

IBC Code

Regulatory Information Conform to the provisions of ICAO/IATA.

by Air

UN No. 1210

Proper Shipping Name PRINTING INK RELATED MATERIAL

Class 3 Packing Group II

Regulations in Japan

Regulatory Information Complies with the Fire Service Act.

by Road or Rail

Regulatory Information Conform to the provisions of the Ship Safety Law.

by Sea

UN No. 1210

Proper Shipping Name PRINTING INK RELATED MATERIAL

Class 3 Packing Group II

Marine Pollutant Not applicable Liquid Substance Not applicable

Transported in Bulk According to MARPOL 73/78, Annex II, the

IBC Code

Regulatory Information Conform to the provisions of the Civil Aeronautics Law.

by Air

UN No. 1210

Proper Shipping Name PRINTING INK RELATED MATERIAL

Class 3
Packing Group II
130

Emergency Response Guide

Number

Section 15 - REGULATORY INFORMATION

Industrial Safety and Health

Act

Ordinance on the Prevention of Organic Solvent Poisoning Paragraph 1 Article 1 part 4 (Second-class organic solvents, etc.), Enforcement Ordinance 2 of Appendix 6

the standards for work environment monitoring Article 65 part 2-1

Dangerous or Harmful Substances Subject to Be Indicated their Names, etc.

(Article 57 part 1, Order Article 18 part 1 and 2, Attached Table9)

Dangerous or Harmful Substances Subject to Be Indicated their Names, etc.

(Article 57 part 1, Order Article 18 part 1 and 2, Attached Table9)

Dangerous Substances -Flammable substances(Order Article Appended Table 1 part 4)

Hazardous Substances to be notified in terms of Whose Names,etc .(Article 57 part 2 ,Order Article 18 part 2-1and part 2, Attached Table9)

Chromium and its compounds (excluding chromic acid and chromate and dichromate and dichromate) (Trade Secrets)

Hazardous Substances to be notified in terms of Whose Names,etc .(Article 57 part 2 ,Order Article 18 part 2-1and part 2, Attached Table9)

Butanol (Number: 477) (Trade Secrets)

Methyl ethyl ketone (Number: 570) (Trade Secrets)

Materials for special medical examinations and current handling workers(Industrial Safety and Health Act66 2 and Order for Enforcement of Industrial Safety and Health Act Article 22 (i))

Chemical substances that damage the skin, etc., and harmful substances that absorb the skin (List of substances subject to Article 594-2, Paragraph 1 of the Safety and Health Regulations, 0531-9 issued on May 31, Reiwa 4, and 0704-1 and 5 of July 4, Reiwa 5)

Methyl ethyl ketone

Industrial Safety and Health Act(after 2024/4/1)

Dangerous or Harmful Substances Subject to Be Indicated their Names, etc.

(Article 57 part 1, Order Article 18 part 1 and 2, Attached Table9)

Hazardous Substances to be notified in terms of Whose Names,etc .(Article 57 part 2 ,Order Article 18 part 2-1and part 2, Attached Table9)

Chromium and its compounds (excluding hexavalent chromium compounds)(Trade Secrets)

Not applicable

Poisonous and Deleterious Substances Control Act Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof

Not applicable

Act on the Regulation of Manufacture and Evaluation of Chemical Substances Priority Assessment Chemical Substances(Article 2 part 5)

Fire Service Act

petroleums non water-so

Water Pollution Prevention

Act

Narcotics and

Psychotropics Control Act Foreign Exchange and Foreign Trade Act Hazardous Materials Category IV inflammable liquids Class I petroleums non water—soluble Packing Group $\rm I\!I$

Specified substances (article 2, paragraph 4 of the Act, article 3 of

the Enforcement Ordinance)
raw materials for Narcotics or Psychotropics(Appended Table IV part

9, Order Article 4)

Import Trade Control Order Appended Table I part 16

Import Trade Control Order Appended Table II (Import Approval)

Ship Safety Law Aviation Law Flammable liquids(Order Article 3,Appended Table I) Flammable liquids(Order Article 194,Appended Table I)

Section 16 - OTHER INFORMATION

Industrial Safety and Health Act Second-class organic solvents, etc.contain more than 5% of Second-class organic solvents.

In the "15. Applicable laws" column, the materials for which label and SDS will be mandated are also listed. (Substance without a decree number.) Reiwa based on 0111 No. 1 from the Kiankahatsu, on January 11, 2022.)

In the case where "composition and ingredient information" corresponds to the secret of the business, the description of the content is the conventional range display. However, it is possible to notify us separately by the method of information transmission agreed with the customer, such as a confidentiality agreement. For more information, please contact our sales representative.

 $2\mbox{-butanone}$ and methyl ethyl ketone, MEK and ethyl methyl ketone are the same substances.

Act on the Regulation of Manufacture and Evaluation of Chemical Substances

We have a Priority Assessment Chemical Substance posting threshold of 0.1% or more.

The posting of a Priority Assessment Chemical Substance in SDS is as of November 2019 as an effort.

Foreign Exchange and Foreign Trade Act Fire Service Act

Foreign Exchange and In law, printing inks are not approved for export

Poisonous and Deleterious Substances Control The flash point of Class I petroleums is less than 21 $^\circ$ c. The deleterious substances is only applicable to the material, and the mixture is non-applicable.

eterious mixture is non-applicat

Act

RoHS Specified Substance Concentration Substances treated as equipment are exempt from this law. Cd<100ppm Pb, Hg, Cr(VI), PBB, PBDE, DEHP, DBP, BBP, DIBP <1000ppm

Allowable concentration Standards Cited Literature

TLV-TWA: Threshold Limit Values-Time Weighted Average STEL (Short Term Exposure Limit

JIS Z7253:2019

1) International Chemical Safety Cards

2) National Institute of Technology and Evaluation (NITE), Japan

3) Site for Safe Workplace by Ministry of Health, Labour and Welfare, Japan

4) EZSDS (JCDB)

Additional Information about This Product:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.